



TCM3 - TCM4

RFID Cards compatibilities

RFID Cartadis - supported cards		Mono-Frequency			Multi-Freq.
		TCM3-1356 MIFARE	TCM3-125	TCM3-125 HID	TCM4
13.56 MHZ	ISO14443A				
	LEGIC Advant (1)	x			x
	MIFARE Classic, Mini	x			x
	MIFARE Classic EV1	x			x
	MIFARE DESFire Light	x			x
	MIFARE DESFire EV1	x			x
	MIFARE DESFire EV2	x			x
	MIFARE DESFire EV3	x			x
	MIFARE A ATQA 0044/SAK 08	x			x
	MIFARE A ATQA 0044/SAK 20	x			x
	MIFARE A ATQA 0004/SAK 20	x			x
	MIFARE A ATQA 0004/SAK 28	x			x
	MIFARE A ATQA 0002/SAK 18 (JCOP)	x			x
	MIFARE A ATQA 0004/SAK 88 (Gunnebo)	x			x
	MIFARE Plus S, X	x			x
	MIFARE Pro X	x			x
	MIFARE Smart MX	x			x
	MIFARE Ultralight	x			x
	MIFARE Ultralight C	x			x
	MIFARE Ultralight EV1	x			x
	HID iCLASS SEOS	x			x
	IZLY (2)				x
	ISO14443B				
	Calypso				x
	Korrigo				x
	HID iCLASS (1)				x
	ISO18092				
	NFC Forum Tag Type 1-5	x			x
	NFC Peer-to-Peer	x			x
	Sony FeliCa	x			x
	ISO15693				
	HID iCLASS (1)				x
	HID iCLASS SE/SR/Elite (1)				x
ICODE SLI				x	
LEGIC Advant (1)	x			x	
Cartadis ID					
Identification with the NFC of an Android smartphone can be performed using the CartadisID application available for free on the store	x			x	

(1) UID Only (2) TCM4 Izly

RFID Cartadis - Supported cards	
125 kHz / 134.2 kHz	EM4100, 4102, 4200
	EM4305
	FDX-B, EM4105
	HID DuoProx II (1336) (1)
	HID ISO Prox II (1386) (1)
	HID Micro Prox (1391) (1)
	HID ProxKey III (1346) (1)
	HID Prox (1)
	HID Prox II (1326) (1)
	StartProx
	HITAG 1, 2, S
	Indala (log and short format)
	Biphase
	Nedap
	Pyramid

(1) UID Only

Mono-Frequency			Multi-Freq.
TCM3-1356 MIFARE	TCM3-125	TCM3-125 HID	TCM4
	x		x
	x		x
	x		x
		x	x
		x	x
		x	x
		x	x
		x	x
		x	x
	x		x
	x		x
	x		x
	x		x
	x		
	x		

Specifications for TCM3 and TCM4

- ✓ Fitted with indicators and buzzer for power-on and reading.
- ✓ The interface operates up to 10cm (according to the transponder).
- ✓ Dimensions: L = 80 mm; H = 50 mm; Depth = 15 mm.
- ✓ Weight = 50 g.
- ✓ Identification with the NFC of an Android smartphone can be performed using the CartadisID application available for free on the store (only on TCM3-1356 MIFARE and TCM4).
- ✓ A configuration tool, standard supplied, enables transformation filters of the card identifiers to be installed.

